

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

LIQUID O2 TRANSFILLS, INC. 1335 NW 98TH COURT # 8,9 MIAMI, FL 33172

EMERGENCY CONTACT: TOLL FREE 1-866-569-3455

TEL:(305)477-1919 SUBSTANCE: HELIUM

TRADE NAMES/SYNONYMS:

MTG MSDS 48; HELIUM GAS; HELIUM COMPRESSED; HELIUM-4; ATOMIC HELIUM; UN

1046; He; MAT10640; RTECS MH6520000 CHEMICAL FAMILY: inorganic, gas

CREATION DATE: Jan 24 1989 **REVISION DATE:** Jun 17 2004

2. COMPOSITION, INFORMATION ON INGREDIENTS

COMPONENT: HELIUM CAS NUMBER: 7440-59-7 PERCENTAGE: 100.0



3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4): HEALTH=0 FIRE=0 REACTIVITY=0

EMERGENCY OVERVIEW:

COLOR: colorless



PHYSICAL FORM: gas

ODOR: odorless

MAJOR HEALTH HAZARDS: difficulty breathing

PHYSICAL HAZARDS: Containers may rupture or explode if exposed to heat.

POTENTIAL HEALTH EFFECTS:

INHALATION:

SHORT TERM EXPOSURE: nausea, vomiting, difficulty breathing, irregular heartbeat, headache, fatigue, dizziness, disorientation, emotional disturbances, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

LONG TERM EXPOSURE: no information is available

SKIN CONTACT:

SHORT TERM EXPOSURE: frostbite

LONG TERM EXPOSURE: no information is available

EYE CONTACT:

SHORT TERM EXPOSURE: frostbite, blurred vision **LONG TERM EXPOSURE:** no information is available

INGESTION:

SHORT TERM EXPOSURE: ingestion of a gas is unlikely **LONG TERM EXPOSURE:** ingestion of a gas is unlikely

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

SKIN CONTACT: Wash exposed skin with soap and water.

EYE CONTACT: Flush eyes with plenty of water.

INGESTION: If a large amount is swallowed, get medical attention.

NOTE TO PHYSICIAN: For inhalation, consider oxygen.



5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Negligible fire hazard. Containers may rupture or explode if exposed to heat.

EXTINGUISHING MEDIA: carbon dioxide, regular dry chemical Large fires: Use regular foam or flood with fine water spray.

FIRE FIGHTING: Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile).

6. ACCIDENTAL RELEASE MEASURES

OCCUPATIONAL RELEASE:

Stop leak if possible without personal risk. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

7. HANDLING AND STORAGE

STORAGE: Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE LIMITS:

HELIUM:

ACGIH (simple asphyxiant)

VENTILATION: Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

EYE PROTECTION: Eye protection not required, but recommended.

CLOTHING: Protective clothing is not required.



GLOVES: Protective gloves are not required.

RESPIRATOR: Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.

Any self-contained breathing apparatus with a full facepiece.

PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: gas

COLOR: colorless **ODOR:** odorless **TASTE:** tasteless

MOLECULAR WEIGHT: 4.0026 MOLECULAR FORMULA: He **BOILING POINT:** -452 F (-269 C)

FREEZING POINT: -458 F (-272 C) @ 26 atm VAPOR PRESSURE: 1719 mmHg @ -268 C

Page 4 of 6

VAPOR DENSITY (air=1): 0.138 **SPECIFIC GRAVITY:** Not applicable

DENSITY: 0.1785 g/L @ 0 C

WATER SOLUBILITY: 0.94% @ 0 C

PH: Not applicable

VOLATILITY: Not applicable

ODOR THRESHOLD: Not available **EVAPORATION RATE:** Not applicable VISCOSITY: 0.02012 cP @ 26.8 C

COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable

SOLVENT SOLUBILITY:

Insoluble: alcohol



10.STABILITY AND REACTIVITY

REACTIVITY: Stable at normal temperatures and pressure.

CONDITIONS TO AVOID: Protect from physical damage and heat. Containers may rupture or explode if exposed to heat.

INCOMPATIBILITIES: No data available. **HAZARDOUS DECOMPOSITION:**

Thermal decomposition products: miscellaneous decomposition products

POLYMERIZATION: Will not polymerize.

11.TOXICOLOGICAL INFORMATION

Not available

12.ECOLOGICAL INFORMATION

Not available

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations.





14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

PROPER SHIPPING NAME: Helium, compressed

ID NUMBER: UN1046

HAZARD CLASS OR DIVISION: 2.2 LABELING REQUIREMENTS: 2.2

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

SHIPPING NAME: Helium, compressed

UN NUMBER: UN1046

CLASS: 2.2

15. REGULATORY INFORMATION

U.S. REGULATIONS:

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Not regulated. SARA TITLE III SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30): Not regulated.

SARA TITLE III SECTION 304 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.40): Not regulated.

SARA TITLE III SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40 CFR 370.21):

ACUTE: Yes CHRONIC: No FIRE: No

REACTIVE: No

SUDDEN RELEASE: Yes

SARA TITLE III SECTION 313 (40 CFR 372.65): Not regulated. OSHA PROCESS SAFETY (29CFR1910.119): Not regulated.

STATE REGULATIONS:

California Proposition 65: Not regulated.

CANADIAN REGULATIONS: WHMIS CLASSIFICATION: A. NATIONAL INVENTORY STATUS:



U.S. INVENTORY (TSCA): Listed on inventory.
TSCA 12(b) EXPORT NOTIFICATION: Not listed.
CANADA INVENTORY (DSL/NDSL): Not determined.

16. OTHER INFORMATION

©Copyright 1984-2006 MDL Information Systems, Inc. All rights reserved.

LIQUID O2 TRANSFILLS, INC. MAKES NO EXPRESS OR IMPLIED WARRANTIES, GUARANTEES OR REPRESENTATIONS REGARDING THE PRODUCT OR THE INFORMATION HEREIN, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR USE. LIQUID O2 TRANSFILLS, INC. SHALL NOT BE LIABLE FOR ANY PERSONAL INJURY, PROPERTY OR OTHER DAMAGES OF ANY NATURE, WHETHER COMPENSATORY, CONSEQUENTIAL, EXEMPLARY, OR OTHERWISE, RESULTING FROM ANY PUBLICATION, USE OR RELIANCE UPON THE INFORMATION HEREIN.